For Earth, For Life

Kubota

Z

KUBOTA ZERO-TURN MOWER Z2-481

The residential mower that performs like a professional

Comfort with built-in safety

For customers considering a zero-turn mower probably the key criteria would be manoeuvrability and performance. Add to that wish list comfort and reliability and you have the Z2-481 mower from KUBOTA.

Kubota is a name synonymous with the ground care industry and the range of equipment they manufacture. The Z2-481 has all the hallmarks of Kubota's long and renown reputation within this industry sector.

Kubota stake their reputation on quality and reliability by offering 2-years or 300 hours peace of mind warranty.*

*** 2-years or 300 hours whichever comes first. Contact your authorised Kubota dealer for further details.**

#Mission

First of all residential

For private large garden owners Z2-481 guarantees general cutting without delay or time consumption around trees and other obstacles within a large grassed area. Reasons why the Z2-481 is the correct choice

- 360° turning technology: lets you mow around obstacles with incredible ease, making every mowing manoeuvre more efficient.
- Unsurpassed comfort: K-ride deluxe fully adjustable seat with suspension adjustment. Anti-vibration floor plate and drive levers.
- Quick, easy deck adjustment: Once the cutting height is set, simple pedal operated raise/lower of the cutting deck.
- Full protection: ROPS frame which can be folded down. Seat belt. Rear bumper bar to prevent damage to the rear and engine compartment.

#Safety

The complete zero-turn mower with everything built-in

Safety first
ROPS protection and seat belt ensures operator safety when working on inclines. The ROPS is foldable allowing the machine to be stored in a low entrance building or when cutting under low branches.

All major operating controls grouped together
The console is contoured to allow the controls to be at the correct angle for ease of use.

Rear end protection
A rear bumper bar protects the area from accidental damage. A rear trailer towing pin expands the machine's versatility.

Outstanding comfort
A fully adjustable deluxe seat. With deep padded back rest armrests, padded grip drive levers and a spacious platform floor area makes the Z2-481 a truly pleasurable experience.

#Complete package

Deck operation simply the best

K-Lift. Deck raise/lower control
Foot operated pedal allows the operator to raise the deck if required. Releasing the pedal will return the deck to the selected cutting height every time. The angle of the pedal ensures comfortable operation.

Quick dial deck height adjustment
Simply turning the dial adjusts the cutting height by ¼" (6 mm) increments. For transportation set the dial in the highest position.

Anti-vibration dampers
The floor plate is not only removable allowing access to the deck drive belts but is also mounted on rubber dampers which removes any vibration that might be felt through the floor. The drive levers are also anti-vibration to remove any discomfort felt through your hands.

K-Ride comfort system
The K-ride suspension system can be set to suit the individual operator.

Storage compartment
Covered storage keeps out dust and prevents items from falling out. A secure drinks holder is conveniently located.

#Performance

Power equates to performance

You need the power to achieve the performance.

V Twin petrol engine
Powered by Kawasaki. The design of V twin engines allows them to run quieter and smoother with less vibrations than traditional single cylinder engines.

Easy access encourages regular checks
A lift-up flap exposes the air filter which can be quickly removed and cleaned. The engine oil dipstick is incorporated into the filler cap and can be effortlessly removed and checked.

Push button start
A key fob allows easy one-handed operation of the choke and engine start switch.

Excellent weight distribution Low profile tyres ensure no damage or compaction of the turf. Stylish wheel rims add to the sleek look of the Z2.481.

Transmission drive and turning within your grasp

Ultimately zero turn mowers are bought for their unique ability to turn with zero turning radius. The drive motion levers operate two independent hydrostatic units which control the drive wheels. The anti-vibration levers with comfortable grip pads provides the operator with complete control.

Rugged construction with professional cut finish.

High strength welded steel deck offers the durability required for these operations.

48” / 1220mm side discharge deck
Side discharge is particularly effective in longer, dense, or moist grass as there is limited build-up on the underside of the mowing deck.

Off-set front wheels
The front wheels are off set to reduce flattening the grass before cutting.

Mulching kit available
A mulching kit can be fitted to the standard deck which cuts and feeds the chopped grass back into the turf.

Welded steel construction
High strength welded steel deck offers the durability required for these operations.

Cutting blade operation
The design of the blades and contour of the cutting chamber not only enhances the cutting quality, but also the airflow to provide a fast and effective grass discharge.

#Let's summarize

The Kubota Z2-481 residential mower that performs like a professional.

And here's why.

Ultimate comfort
Deluxe deep padded, fully adjustable seat. K-Ride with adjustable suspension, anti-vibration floor plate and drive levers.

Deck adjustment and operation
K-Lift foot control lever allows quick and easy lifting/lowering of the deck. Cutting height dial adjustment at the operator's fingertips.

Powerful, smooth, quiet running engine
V-Twin air-cooled petrol engine not only produces the power back-up required, but the design enhances the fuel efficiency.

Transmission drive with comfort and precision
The drive levers are not only comfortable to operate, but they are also responsive to the operational requirements. Superb reaction to obstacle manoeuvres.

Robust deck construction and fine cut finish
High strength welded steel deck. The shape of the cutting chamber together with the durable cutting blades ensure a high quality cut.

2-years / 300 hours warranty
Kubota stands by its statement of providing high quality, reliable produces with one of the best warranty periods on the market.

#Technical data

Model		Z2.481
Engine		V3800-CR-TIE5
Manufacturer		Kawasaki
Model		FR651V
Emissions	Stage	5
Cylinder	n°	90° V-twin
Displacement	cc	726
Fuel system		Unleaded petrol
Ignition system		Electronic spark ignition
Cooling system		Air
Gross power (SAE J1995)	Hp/kW	21.5 / 16.0
Engine speed (Rated)	rpm	3600
Engine hand accelerator		•
Fuel tank capacity	litres	16
Fuel gauge		Sight Window type
Transmission		
Transmission type		Hydrostatic Transmission
Forward speed range	km/h	0 – 12.9
Reverse speed range	km/h	0 – 6.3
Operator platform		
Seat		21» Deluxe High Back Seat w/ armrests w/ 1.5» stroke suspension
Hour meter		•
Foldable ROPS		•
Drinks holder		•
Storage box		•
Towing hitch		•
Mower deck		
Deck lifting / lower		Mechanical Foot Lift Pedal
Deck mounting		Quick connect, parallel linkage
Discharge direction		Side
Cutting width	mm	1219 (48»)
No. of blades		3
Cutting height range	mm	38 – 114 (1.5" – 4.5")
Cutting height increments	mm	6 (0.25")
Adjustment of Cutting Height		Dial adjustment system
Anti-scalp rollers		Fixed
Brakes and steering		
Parking brake		•
Parking brake engagement		Console lever
Steering and driving operation		2 hand levers with height and angle adjustment
PTO		
PTO drive system		Belt
Drive clutch type		Electro-magnetic
Dimensions and weights		
Front tyres		13x6.5-6 Smooth, semi-pneumatic
Rear tyres		22x10.0-14 Turf, low profile
Wheelbase (A)	mm	1195
Overall length (B)	mm	2006
Overall height (With ROPS upright) (C)	mm	1738
Overall height (With ROPS folded)	mm	1240
Overall Width (Without mower deck) (D)	mm	1207
Overall Width (With mower deck - side discharge) (E)	mm	1552
Minimum ground clearance - with mower deck (F)	mm	110
Total weight (With mower deck)	kg	391

• = standard

Kubota (U.K.) Limited
Dormer Road Thame, Oxfordshire, OX9 3UN

http://www.kubota.co.uk

This publication may not be reproduced in whole or in part in any form without the prior written consent of KUBOTA. It corresponds to the status at the time of going to press. The manufacturer reserves the right to change technical specifications without notice. Some of the parts shown in the publication are optional and are not part of the standard equipment. Information on warranty and safety as well as further product information can be obtained from the responsible KUBOTA authorized dealer.

v_1/2023